



- NOTES:**
1. D.A.R.B. VALVE SHOWN IN "NORMAL" OPERATING POSITION.
  2. TO BYPASS CYLINDER, MANUALLY POSITION SPOOL (WITH A SPANER) TO THE POSITION INDICATING "BYPASS"
  3. CARTRIDGES NOT NECESSARILY AS SHOWN.  $\triangle$

ALL DIMENSIONS, TECHNICAL DATA AND INTELLECTUAL INFORMATION ARE PROPERTY OF JASTRAM ENGINEERING LTD. THEY ARE NOT TO BE COPIED, REPLICATED OR USED WITHOUT THE WRITTEN CONSENT OF JASTRAM ENGINEERING LTD.

TOLERANCES:		(UNLESS SPECIFIED OTHERWISE)	
XX	± 0.1	FRACTION	± 1/64
XXX	± 0.01	ANGULAR	± 0.5 DEG
XXXX	± 0.005	SURFACE FINISH	$\checkmark$
ALL DIMENSIONS IN INCH (mm)			

C	26-06-97	SEE DCN 970034	
B	03 20 95	SEE DCN 950017	LL.
A	03.13.90	SEE D.C.N: 90 0006	J.G.
REV.	DATE	DRAWING / DESIGN CHANGE NO.	BY
<b>Jastram</b>		JASTRAM ENGINEERING LTD. 136 WEST 3rd Street North Vancouver, B.C. Canada V7M-1E8 Tel: (604) 986-0714 Fax: (604) 986-0334	
DATE:	01.26.90	SCALE:	NTS
DRAWN:	J.G.	APPROVED:	LL.
TITLE:	D.A.R.B. VALVE O.A.D. (10, 20 & 30 GPM)		DRAWING NUMBER: C-42-10.01